

SCU11-KVM

79111-KVM Data Sheet

The SCU11-KVM converts a 4K@60Hz 4:4:4 (max) USB-C video input into an HDMI video output, and supports USB 3.1 Gen2 data transfer speeds and 60W charging on the USB-C input. The converter includes three USB 3.1 ports for connecting peripheral devices and a Gigabit Ethernet LAN port for tunneling network to a connected USB-C laptop. The SCU11-KVM is plug-and-play, with no drivers or software required.

Features:

- USB-C input with 60W charging and Ethernet tunneling
- Internal USB 3.1 hub connected to USB-C input
- Supports up to 4Kx2K @ 60Hz resolutions
- Plug-and-play operation; no additional software or drivers needed



SCU11-KVM

79111-KVM Technical Specifications

Input	1x USB-C (USB3.1, Gen 2)
Input Resolution	Up to 4Kx2K @ 60Hz 4:4:4
Output	1x HDMI (Type-A, Female)
Output Resolution	Up to 4Kx2K @ 60Hz 4:4:4
Compliances	HDMI: 2.0 HDCP: 2.3 (backwards-compatible)
USB	3x USB Device (Type-A, Female, USB 3.1 Gen 1) 1x USB-C (USB 3.1 Gen 2)
Ethernet	1x RJ45 (10/100/1000BaseT)
Bandwidth	18Gbps
Operating Temperature	14 ~ 131°F (-10 ~ 55°C)
Storage Temperature	-13 ~ 158°F (-25 ~ 70°C)
Relative Humidity	10 ~ 90%
Power Supply	DC 24V, 5A
USB-C Power Delivery	60W (max)
Power Consumption	68W (max)
Product Dimensions	5.7" (145mm) x 3.15" (80mm) x 0.87" (22mm)
Product Weight	1.26 lbs. (270g)

Specifications are subject to change without notice

