

CB2-A Ceiling Box

78039 Data Sheet

TEKVOX's Plenum-rated CB2-A ceiling box provides an enclosure for mounting non-Plenum rated A/V components and equipment in drop ceilings and air-return Plenums. The CB2-A includes power, HDMI, and RS232 ports for connecting a projector without needing to modify any drop-ceiling tiles. The CB2-A also provides outlets for powering HDBaseT transmission equipment, system controllers, audio amplifiers, and more.

The CB2-A is a larger variant of TEKVOX's original CB1-A 2x1 ceiling box, providing even more space for mounting components while maintaining the same level of quality and convenience.

Features:

- 2' x 2' ceiling box for installation in standard 2' x 2' drop ceiling grids
- Plenum-rated (conforms to UL 2043 Fire and Safety test)
- Six internal power outlets
- Two removable equipment trays for mounting non-Plenum-rated equipment
- Power, HDMI, and RS232 ports on underside for connecting projector
- Customized lid design available for additional cost
- Includes all necessary mounting hardware



CB2-A Ceiling Box

78039 Technical Specifications

Internal Connections	6 NEMA 5-15 US Power Outlets
External Connections	1 NEMA 5-15 US Power Outlet 1 HDMI (19-pin, Female) 1 RS232 (RJ12, Female)
Certifications	UL 2043 Plenum Fire Safety UL 2416
Power Rating	120VAC @ 60Hz, 15A max (total)
Product Dimensions	24" (610mm) x 24" (610mm) x 6" (152.4mm)
Product Weight	26.7 lbs. (12.1kg)

Specifications are subject to change without notice