

# ShareView Wireless

## 79060-WPS Data Sheet

ShareView Wireless offers the advanced functionality of a 4K multiview switcher, combined with the convenience of a wireless presentation system. It allows multiple users to share content at once, and supports 4K resolution, all without requiring any wires or cabling. Users can plug in one of the HDMI or USB-C wireless transmitters to share their screen, without needing to download any software. ShareView Wireless also supports Apple AirPlay, and the Android WirelessMedia2 app, for sharing from tablets & smartphones.

Unlike other wireless presentation systems, ShareView Wireless is plug-and-play, able to switch quickly between sources. The wireless transmitters are powered via the connected device's USB port, and so do not require charging. With the base unit connected to a touchscreen, users can control connected laptops through that touchscreen, even in multiview.

### Features:

- Supports resolutions up to 4Kx2K @ 60Hz
- Displays up to four sources simultaneously
- Available with HDMI and USB-C wireless transmitters
- Controllable via built-in touch controls or Telnet/RS232
- Three levels of wireless network security
- Touchscreen control of connected laptops
- Operates without the need for a network connection

Part No.	Description
79060-WPS	Base unit only
79060-WPS2	2 Dongles
79060-WPS4	4 Dongles
79060-HDMI	HDMI Dongle
79060-USB-C	USB-C Dongle



ShareView Wireless Base Unit



HDMI & USB-C Wireless Transmitters



AirPlay for Apple Devices



WirelessMedia2 app for Android devices

# ShareView Wireless

## 79060-WPS Technical Specifications

<b>Video Output</b>	1 HDMI (19-pin, Female)
<b>Supported Resolution</b>	4Kx2K @ 60Hz, 4Kx2K @ 30Hz, 1080p @ 60Hz Airplay for IOS Devices: 1080p @ <60Hz WirelessMedia2 app: 1080p @ <60Hz Show-Me Buttons: 1080p @ <60Hz
<b>Audio Input</b>	AirPlay, Windows/MAC, WMH
<b>Audio Output</b>	1 Analog Audio (3.5mm, Female)
<b>Network Ports</b>	1 1000Mbps (RJ45, Female) 1 100Mbps, (RJ45, Female)
<b>USB Ports</b>	1 USB3.0 (Type-A, Female) 1 USB2.0 (Type-A, Female) 1 USB-C (Female)
<b>Serial Ports</b>	1 RS232 (3-pin Phoenix)
<b>Maximum number of windows on-screen simultaneously</b>	≥4+14 (4 main windows + 14 thumbnail windows)
<b>Maximum number of simultaneous connections</b>	≥16
<b>Wireless Data Rate</b>	Up to 1200Mbps
<b>Video Playback Framerate</b>	20 ~ 60 FPS
<b>Latency</b>	20 ~ 100 ms
<b>Frequency Band</b>	2.4 GHz & 5 GHz
<b>Wireless Transmission Protocol</b>	WIFI IEEE 802.11 a/g/n/ac
<b>Compliances</b>	HDMI 1.4 / 2.0 HDCP 1.4 / 2.2 POE IEEE802.3af
<b>Temperature</b>	-4 ~ 140°F (-20 ~ 60°C)
<b>Humidity</b>	20 ~ 90%
<b>Power Supply</b>	Input: 120/240VAC Output: 12V DC
<b>Power Consumption</b>	10W (max)
<b>Product Dimensions</b>	6.5" (165mm) x 4.9" (125mm) x 0.96" (24.5mm)
<b>Product Weight</b>	0.4 lbs (200g)

Specifications are subject to change without notice

