

# SCU11-KVM

## 79111-KVM Data Sheet

The SCU11-KVM converts a 4K@60Hz 4:4:4 (max) USB-C video input into an HDMI video output, and supports USB 3.1 Gen2 data transfer speeds and 60W charging on the USB-C input. The converter includes three USB 3.1 ports for connecting peripheral devices and a Gigabit Ethernet LAN port for tunneling network to a connected USB-C laptop. The SCU11-KVM is plug-and-play, with no drivers or software required.

### Features:

- USB-C input with 60W charging and Ethernet tunneling
- Internal USB 3.1 hub connected to USB-C input
- Supports up to 4Kx2K @ 60Hz resolutions
- Plug-and-play operation; no additional software or drivers needed



# SCU11-KVM

## 79111-KVM Technical Specifications

<b>Input</b>	1x USB-C (USB3.1, Gen 2)
<b>Input Resolution</b>	Up to 4Kx2K @ 60Hz 4:4:4
<b>Output</b>	1x HDMI (Type-A, Female)
<b>Output Resolution</b>	Up to 4Kx2K @ 60Hz 4:4:4
<b>Compliances</b>	<b>HDMI:</b> 2.0 <b>HDCP:</b> 2.3 (backwards-compatible)
<b>USB</b>	3x USB Device (Type-A, Female, USB 3.1 Gen 1) 1x USB-C (USB 3.1 Gen 2)
<b>Ethernet</b>	1x RJ45 (10/100/1000BaseT)
<b>Bandwidth</b>	18Gbps
<b>Operating Temperature</b>	14 ~ 131°F (-10 ~ 55°C)
<b>Storage Temperature</b>	-13 ~ 158°F (-25 ~ 70°C)
<b>Relative Humidity</b>	10 ~ 90%
<b>Power Supply</b>	DC 24V, 5A
<b>USB-C Power Delivery</b>	60W (max)
<b>Power Consumption</b>	68W (max)
<b>Product Dimensions</b>	5.7" (145mm) x 3.15" (80mm) x 0.87" (22mm)
<b>Product Weight</b>	1.26 lbs. (270g)

Specifications are subject to change without notice

